



SkyTher
ceramic

We Believe in Quality



SkyTher
ceramic

200x1000mm

200x1200mm

LUXURY

WOODEN PLANK





Maintaining authenticity is a challenge indeed for many; especially when it involves replicating wooden floor designs. Wooden surfaces come with their own individual characteristics, a product of environmental conditions that induce unique patterns found in tree trunks. The uniqueness of such patterns pose a 'unique' challenge to us, which we have taken in our stride. Not only we ensure the quality and aesthetics of designs, but also the resultant feel as if one were walking upon a genuine wooden floor. With superb tile printing techniques, we have come up with unique designs, keeping in mind customer preferences and choices, as also to provide a heady mix of different sizes and design ranges to choose from. For those with a distinct taste for wooden flooring, our collections will surely invite a ponderous gaze that doesn't cease to stop.





2001 -R-6



2004 -R-16



2005 -R-6



African black wood- -R-4



alacia black-R-4




American Elm wood-R-5




Antique Wood almond -R-9



ANTIQUE WOOD beige-R-9



Antique Wood Brown-R-9





ARJUN WOOD BROWN-R-10



BANANA WOOD BEIGE -R-4



BANANA WOOD CHOCO -R-4



BANANA WOOD CREMA -R-5



BANANA WOOD SANDAL -R-5



BARK WOOD BROWN-R-5



Beige Brich Wood-R-5



bosco beige-R-9




bosco almond-R-9



bosco brown-R-9





bosco natural -R-9



BOSTAN GREY -R-9



BOSTAN SANDAL -R-9



BOSTAN WHITE-R-7



Brich Forest-R-4



Brown Birch Wood-R-6



Cherry Wood-R-6




Chinaberry Wood-R-5




classic wood-R-6



Coco Wood-R-4



cocon wood gris -R-6



COCON WOOD MANGO -R-6




COCON WOOD NATURAL -R-6





COCON WOOD PEACH- -R-6



coffie brown -R-3



coral SATVARIO -R-10






coral crara -R-10



corial beige-R-8



Corson honey pine-R-6



Corson Wood dark grey-R-6



Corson Wood gold-R-6



Corson Wood Light grey-R-6



Corson Wood-R-6




Cottage Beige-R-4




Cottage Wood-R-46



Crema -R-3



decor beige -R-8



decor brown -R-8



EBONY WOOD GOLD -R-6



Emboss Wood -R-4





Forest Wood-R-5



Galex White -R-5



grey Brich Wood -R-5



HIMALAYAN SNOW -R-12



Julyo Wood -R-4



Kalida Wood Crema -R-6



Kashmir rose -R-4




Latina Brown -R-10



Latina coffie-R-10



Latina Crema -R-10



Latina Grey -R-10



London CREMA -R-10



London natural -R-10



London natural -R-10



London rose -R-5



London walnut -R-10



MAPLE BROWN -R-9



MARVAL BROWN -R-11



NATURAL DRY WOOD -R-5



Neo wood -R-2



peru brown -R-6



PIMLICO WOOD BEIGE -R-3



Pine yellow -R-8



Pine Beige -R-8



Pine Brown -R-8



pine Gray -R-8



pine Gray -R-8



pine red -R-8



Pine white -R-8



PRM 8210 -R-8



PRM 8211 -R-8



REAL COFFFE BROWN-R-8-P-212




Real wood crema-R-8-P-212




Real wood grey-R-8-P-212



Real wood white-R-8-P-212




regal oak -R-8



Rose wood -R-9



ROYAL ALOMND -R-6



Royal WOOD Grey -R-10



ROYAL WOOD BROWN -R-10



Royal Wood Green -R-10



ROYAL WOOD SANDAL -R-10



ROYAL WOOD WHITE -R-10



Sisam wenge-R-8



Solid Wood -R-6



SWISS WALNUT -R-4




Timber Wood -R-5



TORINO TEAK -R-8



Torino Beige -R-8



TTorino Black -R-8



Torino Brown-R-8



Torino Grey-R-8



Torino red-R-8



TORINO SILVER-R-8



Torino White-R-8




Traventine grey-R-1



Traventine White-R-1



Travertino beige-R-1



Walnut Brown-R-7



White Wood-R-4



William Brown-R-6

LAYING INSTRUCTIONS

TILES LAYING INSTRUCTIONS

1. All the tiles must be checked prior to laying for quality, batch no. and shades.
2. Place the surface of the floor to be tiled and allow curing at least two weeks before tiling.
3. While laying, quick tiles from various boxes alternatively, lay them in the desired pattern and make sure that they give an acceptable blend of colour and design. Remember that shade variation is inherent in natural looking tiles.
4. For tiling tiles we recommend to use the best adhesive or cementitious product for the best result.
5. For tiling tiles in floor using conventional methods, we suggest the following instructions:
A. Use cement and sand mortar in the ratio 1:4. Add water to create a consistency paste.
B. Apply 20-25mm of bedding mortar a cover the floor area of 1 Sq. Mtr. at a time.
C. Apply this coat of the mortar on the back of the tile to ensure proper and full bedding. Press gently for even adhesion of the tiles with surface. Do not use any heavy material like brick or hammer to press tile.

6. For tiling the tiles on Goffs, we recommend the use of adhesive or equivalent materials.
7. Allow 2-4 days of bed curing after laying the tiles before fill the joints with grout.
8. We recommend maintaining a joint gap of 1-2mm between the tile to allow possible thermal expansion at later stage.
9. Please note that company will not accept any liability in case of any problems arising out of non-adherence of above laying instructions.

NOTES:

- * All technical specifications in this catalogue are for premium grade materials only.
- * SHADE/SIZE VARIATION are inherent characteristics of ceramics. Certain products purposely have variations that are the part of designs and process. The same have been indicated.
- * It is recommended to blend tiles by mixing tiles from various boxes and check for natural looking tiling.
- * Company's liability is also limited to the material supplied by the company; no other claim is entertained under any circumstances.
- * No complaints shall be entertained regarding the decoration on tiles.

Helpful tips for better aesthetics look (Laying Instructions)

1. For better aesthetic value and for long term guaranteed use, it is strongly recommended to provide 3mm spacer in between the tiles. Without spacer, harmony of the tiles might be disturbed.
 2. Make sure that the design, pattern and the arrow marked on the back side of tiles are in the same direction.
 3. Any product from digital tile must be installed (laid) in the same format.
- * THE COMPANY SHALL NOT BEAR ANY LIABILITY FOR THE PROBLEMS OUT OF NON-FULFILLMENT OF LAYING INSTRUCTIONS AS ABOVE.

Wooden Plank Tile: Demo & Installation

